

FX-2200LCD

The Forza FX Series offers an enhanced level of protection specially designed for your high performance office equipment



Like servers, sensitive electronics and home theater components. It features a coaxial surge protection line and LCD display, in addition to a battery-supported system (UPS), allowing you ample time to save your important information and shut down all your equipment safely during power failures. The FX UPS system comes in two different configurations: 1500VA and 2200VA. Designed for Home Theater / Server & Network

Highlights

- Emergency backup power supply
 - Complete AVR protection
 - System monitoring made simple with a state of the art LCD display
 - Coaxial line protection
 - Network and phone line surge protection
 - ForzaTracker software
 - USB cable included
 - Trusted quality
- Backed by 3- year warranty, limited to 2 years on batteries

2200VA

PROTECTION LEVEL 5

- + Breaker
- + Surge Protector
- + Voltage Protector
- + Voltage Regulator
- + Power Back up



Ideal for

MPN	FX-2200LCD
General	
Capacity	2200VA/1200W
Input	
Nominal voltage	120V
Voltage range	89-145VAC
Frequency	45-65Hz (autosensing)
AC plug style	NEMA 5-15P
Output	
Nominal voltage	120V +/- 10%
Frequency	50/60Hz
Frequency stability	+/- 1Hz battery mode
Waveform	Modified sine wave
Total outlets	8 (NEMA 5-15R)
Full battery / Surge protection outlets	6
Surge protection outlets only	2
Internet protection	RJ-45
Phone/Modem/Fax protection	RJ-11
Coaxial protection	Included
USB management	Included
Battery	
Type and quantity	12V/9Ah (2)
Backup time	81 min**
Recharge time	6 hours to 90% after complete discharge
Voltage regulation	
Automatic voltage regulation	Included
Frequency regulation	
Automatic frequency selection	Included
Line/battery transfer	
Typical transfer time	2-4ms
Low line transfer to battery (120/220V)	89VAC
High line transfer to battery (120/220V)	145VAC
Alarms/ indicators	
Visual indicators	Sounds continuously Easy to read LCD with a blue backlight that displays the battery status, input voltage, output voltage, and operation mode of the UPS
Audible alarm	Battery mode: sounds every 10 seconds Low battery: sounds every second Overload: sounds every 0.5 second Fault: continuous sound
Protection	
Full protection	Line mode: 110%+20%/-10%; shutdown after 5 minutes and go to fault mode. 120%+20%/-10%; shutdown immediately and go to fault mode. Battery mode:120%+20%/-10%; shutdown immediately
Joules	660J
Special features	
"Cold start" option	Included
Auto charge	Included
Environment	
Operating temperature	32-104° F
Storage temperature	5-113° F
Relative humidity	0-90% non-condensing
Audible noise	<40 dB at one meter

MPN	FX-2200LCD
Physical appearance	
Power switch	Included (lighted)
Housing	Flame retardant plastic
Color	Black
Cord length	3ft
Dimensions	15.3x5.6x7.7in
Weight	25lb
Additional information	
Warranty	3 years*

* 2 years on batteries

**Calculated with a single PC plus monitor at 7% load

